

**Quadraplex “Oil-Less” Claw Lab Vacuum Package 15 HP (Fixed Speed or VFD )  
Base Mount Modular with Automatic Purge Control**

**Vacuum Package**

- Four oil-less rotary claw type vacuum pumps with inlet filter and isolation valve for each
- ASME coded vacuum receiver with bypass and manual drain
- Quadraplex control panel with automatic lead/lag controls
- All components completely pre-piped and pre-wired to single point service connections (per module)
- Vibration isolation mountings
- Liquid tight conduit, fittings and junction boxes for all control and power wiring
- All interconnecting piping and wiring is completed and operationally tested prior to shipment (per module)

**Vacuum Pump**

- Oil-less rotary claw pump
- Direct-driven through a shaft coupling
- Air-cooled
- End (ultimate) vacuum = 28" Hg
- Dry-running, with two claw-type, non-contacting rotors
- Sealing fluid not required
- Virtually maintenance-free operation
- High discharge temperature switch
- Oil change required at approximately 5,000 operating hour intervals in the gearbox only
- Built-in, anti-suck-back valve mounted at the pump inlet
- 2 micron inlet filter for removal of particulates

**Vacuum Motor**

- NEMA rated
- C-face
- TEFC
- 208 or 230/460V 3-phase

**Vibration Isolation System**

- Vacuum and motor - fully isolated from the package base by means of a four-point, heavy duty, isolation system
- Minimum of 95% isolation efficiency
- Optional seismically restrained isolators at an additional cost

**Intake/Discharge Piping**

- Vacuum pumps are connected per module
- Inlet check valve on each pump
- Inlet isolation valve on each pump
- Flexible connectors between pumps and manifold
- Flexible connectors for inlet and discharge connections
- Discharge flex connection shipped loose

**Vacuum Receiver**

- Vertical orientation with integrally mounted 3-valve bypass and manual drain
- ASME Code stamped
- National Board Certified
- Rated for a minimum 200 PSIG design pressure
- Vacuum gauge
- Manual drain

**System Health**

- Monitoring and Trending of key components to provide notification of potential issue with the Health of the System
- Vacuum monitoring
- Current monitoring for each motor
- Ambient Temperature monitoring
- Trending of pumps running

**Control System**

- Mounted and wired quadraplex control system
- NEMA 12 and UL 508A labeled
- **75Lv only:** Variable frequency drive to control one pump at a time
- Automatic lead/lag sequencing
- Circuit breakers
  - **75L:** One for each motor with external operators
  - **75Lv:** One external disconnect, but internally one for VFD and one for each motor
- Full voltage motor starters with overload protection
- 120V control circuit transformers for each motor circuit
- Visual and audible reserve unit alarm with isolated contacts for remote alarm
- Hand-off-auto selector switches for reliable back-up
- Automatic alternation of compressors based on a first-on/first-off principle with provisions for simultaneous operation
- Automatic activation of reserve unit if required
- Visual and audible alarm indication for high discharge air temperature shutdown with isolated contacts for remote alarm
- SIGNAL 1™ – touch screen gateway

Standard Screen Displays

- |                        |  |
|------------------------|--|
| + Air level/Runtime    | + Replacement parts                    |
| + Alarm history        | + Troubleshooting guidelines           |
| + Service Indicator    | + Historical trending of system status |
| + Maintenance Schedule | + System Health                        |

- 7” Wide TFT Graphic Touch Screen with Motion Actuated Backlit LED and Bright 65,536 (16-bit) Colors
- Downloadable Trend Information via USB Host Port or Network Device
- 128MB Flash Memory, 64MB DRAM
- Built-in Ethernet Port 10/100 Base-T (RJ45)
- Supports over 100 Communication Protocols including Ethernet IP, and Modbus TCP/IP
- Built-in VNC server allowing remote monitoring of live graphics through standard browser, smart phones & mobile devices
- Share data between HMI and Building Management systems

**Automatic Purge Control**


- Each pump intake is equipped with an automatic purge valve and automatic isolation valve
- Minimum run and purge cycle are controlled via SIGNAL 1 purge control function
- Selection of automatic purge, manual purge, or purge off
- 15 minute purge cycle per pump
- Can be set to exit purge if vacuum falls below a setting

## SPECIFICATION

**75L-44-153 75Lv-44-153**

**75L-44-154 75Lv-44-154**

**75L-44-155 75Lv-44-155**



| Quadraplex Claw Lab Vacuum Package Specification |    |                               |               |                             |                          |            |         |           |                         |            |                         |
|--|----|-------------------------------|---------------|-----------------------------|--------------------------|------------|---------|-----------|-------------------------|------------|-------------------------|
| Model Number                                     | HP | Capacity @19" Hg <sup>2</sup> |               | Package BTU/HR <sup>3</sup> | Noise Level <sup>4</sup> | System FLA |         |           | Receiver Size (gallons) | L (inches) | Package Weight (pounds) |
|  |    | Pump (SCFM)                   | System (SCFM) |                             |                          | 208V (A)   | 230 (B) | 460 V (C) |                         |            |                         |
| 75L-44-153(A/B/C)                                | 15 | 129                           | 516           | 176,000                     | 90.5                     | 158        | 143     | 72        | 120                     | 79         | 4,869                   |
| 75Lv-44-153(A/B/C)                               |    |                               |               |                             |                          |            |         |           |                         |            | 4,919                   |
| 75L-44-154(A/B/C)                                |    |                               |               |                             |                          |            |         |           | 200                     | 84         | 5,024                   |
| 75Lv-44-154(A/B/C)                               |    |                               |               |                             |                          |            |         |           |                         |            | 5,074                   |
| 75L-44-155(A/B/C)                                |    |                               |               |                             |                          |            |         |           | 240                     | 96         | 5,162                   |
| 75Lv-44-155(A/B/C)                               |    |                               |               |                             |                          |            |         |           |                         |            | 5,212                   |

**Notes:**

<sup>1</sup> Normal Operating conditions at a maximum ambient of 105° F. Consult factory for higher ambient conditions.

<sup>2</sup> Capacities are shown with all pumps running.

<sup>3</sup> Package BTU/HR are shown with all pumps running.

<sup>4</sup> Noise levels are shown in dB(A) and reflect all pumps running.

**Statement of Warranty**

**Patton's Medical** warrants all Medical Air packages, to be free of defects in material and workmanship under normal use for a period not to exceed thirty (30) months from date of shipment, or twenty-four (24) months from date of start-up.