Pattons medical

**SPECIFICATION**
**931-U06-OXY-DFOF-C400**

# Hose Assemblies

## General Specifications:

The hose assembly is manufactured with medical grade PVC tubing. The tubing is reinforced with nylon braiding. All ingredients in the formulation of the tube comply with FDA, NFPA 99, and CSA Z305.2 requirements. The maximum working pressure is 200 psi @ 70°F. The fittings are permanently crimped on each end with ferrules.



## Features:

- Variety of lengths and configurations
- Variety of gases
- CE marked and CSA approved
- 100% tested and quality inspected

## Model Numbers:

Hose Assembly: **931 – U06 – OXY – DFOF – C400**

Options:
M: Non-ferrous

Color Code:
U: US
E: ISO

Length (in feet)

Inlet Connection

Outlet Connection

Hose Type:
Standard:
C4: Conductive ¼”
C5: Conductive 5/16” *(E,V, or W only)*
Special:
N4: Non-conductive ¼”
N5: Non-conductive 5/16” *(E,V, or W only)*

**Gas:**
O: Oxygen
A: Medical Air
2: Nitrous Oxide
N: Nitrogen (n/a for PB/CH/Ohmeda)
C: Carbon Dioxide (n/a for PB/CH)
I: Instrument Air(n/a for PB/CH/Ohm)
V: Vacuum
W: WAGD
E: AGSS (ISO version of WAGD)

**Connection Options:**

***Standard Ends:***
DF: DISS Hex Nut
DH: DISS Handtight
DC: DISS Male w/Demand Check
DM: DISS Male
OF: Ohmeda Female
OM: Ohmeda Male
CF: Chemetron Female
CM: Chemetron Male
PF: Puritan Female
PM: Puritan Male

***Special Ends:***
M4: 1/4” MNPT
M2: 1/8” MNPT
F4: 1/4” FNPT
F2: 1/8” FNPT
SF: Schrader Female
SM: Schrader Male
OM: Oxequip Male
MM: Medstar Male
XX: Blank

**Example**: Oxygen 6’ (72”) hose assembly with Female DISS x Ohmeda Female Coupler with US Colors = S-HS-06UO-DFOFC4


T 704 529 5442 W pattonsmedical.com